


Universal
Compatibility

7 Day Programmable or Manual Touch Screen Thermostat

P721UT



For Use On:

- Universal Compatibility for Conventional Heat & AC and Heat Pumps with Up to 2-Stage Heat/ 1 Stage-Cool
- 3 Wire Hydronic (Hot Water) Zone Valves
- Gas Millivolt Heaters

Not For Use On:

- 120/240 VAC Line Voltage Systems
- Dual Fuel Systems

Terminals:

- G, Y1, RC, RH, W1, A, Y2, O, B, W2, C

Ratings:

- 1.5 Amps per terminal at 24 Volts
- Temperature Control 45F to 90F (7C to 32C)

Dimensions:

- 5.375" (136 mm) x 3.375" (86 mm) x 1.125" (28 mm)

UPC Code:

- 0 21079 13960 6 Master Carton - 10 units

Features:

- Each Day Can be Programmed Differently (2 or 4 periods/day)
- Large Display with Blue Backlight
- Speed Slide™ For Easy Programming
- Adjust. Heating and Cooling Limits
- Programmable Key Board Lock
- Programmable Air Filter Monitor
- Selectable Smart Recovery
- Dual Powered (2 AA Batteries Included)
- User Selectable Programmable or Non-Programmable Operation
- Manual Temperature Hold
- Temporary Temperature Override
- Adjustable Temp. Differential Cycle Rate
- Adjustable 2nd Heat Stage Offset Setting
- User Temperature Calibration
- 5/2 Minute Selectable Time Delay
- Battery Free Memory Storage
- 12/24 Hour Clock Display
- Optional Wall Plate Available



PRODUCTS
CORPORATION

6000 Commerce Parkway * Suite I * Mount Laurel, NJ 08054
(800) 628-4309 * Fax (856) 234-7825

7/23/2013

LUXPRO
THERMOSTATS