



Empowering you to work smarter

NRRD Recovery Unit



Light • Fast

One Key Operation

- Easy to use

Twin Cylinder

- Fast recovery

Oil-Free Compressor

- Suitable for all commonly used refrigerants

Purge Function

- Prevent mixing of various refrigerants

High Pressure Protection

- Added safety

Model		NRRD			
Refrigerant Type		Category III: R-12, R-134a, R-401C, R-500 Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-411A, R-411B, R-412A, R-502, R-509 Category V: R-402A, R-404A, R-407A, R-407B, R-410A, R-507			
Power Supply	V / Hz	115V / 60Hz			
Motor	HP	1			
Max Current Draw	A	10			
Compressor		Oil-less, Air-cooled, Piston style			
Automatic Safety Shut-Off		558 psi / 38.5 bar			
Recovery Rate	lbs / min		R-22	R-134a	R-410a
		Direct Vapor	0.49	0.31	0.44
		Direct Liquid	6.17	4.7	6.06
		Push/Pull Liquid	11.60	10.8	12.61
Full Load Amps	A	12			
Dimension	in	18 x 10 x 14			
Weight	lbs	30			

1-YEAR WARRANTY