




**Superior Quality**  
**Superior Service**  
**Superior Value**

## 901/902 Series Flex Duct



### Features and Benefits:

- ❖ Knauf FDM blanket insulation with Ecosse® Technology
- ❖ Greenguard® Certified insulation
- ❖ Tough, tear-resistant jacket
- ❖ Small profile, weather-resistant packaging

## SILVER JACKET 901/902 SERIES

All thermal performance (R-Values) are classified by ETL ( Intertek Laboratories ) in accordance with ADC Flexible Duct Performance and Installation Standards. Using ASTM C-518 (1991), at installed wall thickness, on flat insulation only.

### Construction

**Air Tight Inner Core:** Double lamination of strong polyester encapsulates a steel wire helix.

**Insulation:** Formaldehyde- free Multi-thicknesses (R4,R6,R8) wraps the double layer inner core. Mold and mildew resistance. ECOSE non petroleum base binding Technology.

**Jacket:** Tough and durable Bi-Directional fiber reinforced metalized polyester jacket.

### Product Description

Royal Metal Flexible Duct Conforms to U.L. standard 181 for Class 1 Flexible Air Ducts, and is manufactured with a Bi-directional reinforced fiberglass scrim with a metalized out jacket. The three products have an air-tight inner core designed to operate at medium to low pressures in HVAC systems. The product is insulated to meet geographic building code requirements. Narrow wire spacing on core allows for low friction loss and low operating cost. Insulation Formaldehyde free, mold and mildew resistance with ECOSE Technology prevents itching when installing.


### Application and Compliances

Product is designed for indoor use as a supply or return air duct in low to medium pressure residential and commercial heating and air conditioning systems. All three R values can be used to complete air duct systems', branch duct, connecting to mixing boxes, diffusers, room inlets, or other devices. R factor requirements are determined by geographic building codes. UL 181, NFPA 90A & 90B



**Superior Quality**  
**Superior Service**  
**Superior Value**

## 901/902 Series Flex Duct



### PRODUCT DATA:

**Packaging:** product available in boxes or bags.  
**Available Sizes:** 4",5",6",7",8",9",10",11",12",14",16",18",20" diameter  
**Standard:** ETL listed/Approved to UL 181

### PERFORMANCE DATA:

**Intertek Testing Service**  
**Conforms to U.L. Standard 181**  
**Maximum Rated Velocity: 5500 FPM**  
**Maximum Rated Positive Pressure: 10" W.G. 4" through 20" I.D.**  
**Maximum Rated Negative Pressure: 3/4" W.G. 4" through 20" I.D.**  
**Flame Spread: 25 max**  
**Smoke Developed: 50 max**  
**Temperature Range: -20°F, 250°F continuous**  
**Code Compliance: NFPA 90A and 90B, UL 181**

**See installation instructions for joint treatments**

Warranty: Royal Metal Products warrants that its flexible air duct will be free from defects in material and factory workmanship for a period of ten years from date of manufacture. This warranty applies only to the ducts installed in accordance with Air Duct Council (ADC) flexible duct performance and installation standards and within the conditions specified in published performance data. The warranty is for exchange of duct only and does not include installation. Royal Metal Products shall have no liability to the buyer or third party for any special, incidental or consequential damages.