

## NRDC4M Recovery Unit

# 4 - Cylinder




3/8" Inlet Port  
1/4" Outlet Port




Dual Oil-Free Compressors



3 High-Speed Cooling Fans



Digital Backlit Display



Purge Function



Brushless DC Technology

## World's First DC Inverter 4-Cylinder Recovery Unit Fastest · Most Powerful

### 4-Cylinder for Powerful Recovery

- Up to 40% faster than 2-cylinder unit
- Oversized inlet port for faster recovery

### Large Digital Display

- Easy-to-read large LCD display
- Backlit for clarity

### Super-Efficient Condenser

- Over-sized micro-channel coil
- 3 cooling fans

### Dual Oil-Free Compressors

- Suitable for all commonly used refrigerants

### Brushless DC Motor

- More efficient

### Acceleration Knob Design

- To achieve faster vapor recovery

Model		NRDC4M			
Refrigerant Type		Category III: R-12, R-134a, R-401C, R-500 Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-502, R-509 Category V: R-402A, R-404A, R-407A, R-407B, R-410A, R-507			
Power Supply	V/Hz	115V/60Hz			
Motor	HP	1.5			
Max Current Draw	A	12			
Compressor		Oil-less, Air-cooled, Piston style			
Automatic Safety Shut-Off		558 psi/38.5 bar			
Recovery Rate	lbs/min		R-22	R-134a	R-410A
		Direct Vapor	0.93	0.34	1.02
		Direct Liquid	7.16	4.95	9.20
		Push/Pull Liquid	13.29	10.20	18.41
Inlet/Outlet Port	in	Inlet 3/8", Outlet 1/4"			
Dimension	in	17" x 10.7" x 12.2"			
Weight	lbs	41.9			

**2-YEAR WARRANTY**